



ADVANCED FUEL SOLUTIONS, INC.

Greenburn®

Premium Heating Oil Package

Greenburn® is a multifunctional emissions control additive package developed specifically to enable oil companies to market a premium heating oil. Greenburn® has also been formulated using an optimized anti-oxidant system designed to protect storage and distribution systems from sediment, build up and filter blockage associated with both distillates and biodiesel blended fuels.

Addition

Greenburn® is designed for handling at ambient temperatures and direct injection to heating oil is the standard route. The shelf life recommendation is 12 months.

For personal safety, first aid, storage and handling, see the safety data sheet (SDS) for product specific

Greenburn® is a fuel additive that provides the following functional and performance benefits:

- Reduces soot and particulate emissions
- Reduces carbon monoxide emissions
- Improves fuel efficiency/economy
- Improves system cleanliness both in burners and injector nozzles
- Extends maintenance intervals
- Improves Bioheat® fuel blends storage stability up to 20%
- Corrosion control
- Lubricity enhancement and pump protection



ADVANCED FUEL SOLUTIONS, INC.

AFS Technical Team

Toll-free: 866-213-3219

Office: 978-258-8360

Email: info@yourfuelsolution.com

85 Flagship Dr. North Andover, MA 01845

Typical Properties

Appearance	brown liquid
Specific Gravity.....	0.922
Density, lb./gal, 60°F.....	7.68
Flash Point, PMCC	132°F
Viscosity, cSt @ 40°C.....	3.0
Pour Point, °F	-40
Recommended Treat Rate.....	1:2,000